

# Fireslide SV-E60

CE  E60




2023.27 (eng)

## Fire-resistant vertically sliding window

Fire-resistant, vertically sliding, electrically operated window. The sliding window has a frame made in powder coated steel. The SV-E60 model is specially designed for installations in which demands are made on fire resistance class E15-E60 and it is provided with 6 mm Pyran S fire resistant glass. It is automatically locked in the closed position and at 50 mm intervals across the opening. Operated by control switch with hold to run buttons.



## DESIGN



Window with  
one sliding  
section

## TECHNICAL INFORMATION

|                          |   |
|--------------------------|---|
| NAME                     | Fireslide SV-E60  |
| DESCRIPTION              | Fire-resistant, vertically sliding, electrically operated window.   |
| WIDTH                    | 600 - 1160 mm.  |
| HEIGHT                   | 800 - 2120 mm.  |
| FRAME THICKNESS          | 80 mm.  |
| WIDTH SIDE POSTS         | 60 mm.  |
| HEIGHT TOP PROFILE       | 70 mm.  |
| HEIGHT OF BOTTOM PROFILE | U-profile 25 x 25 x 25 mm.  |
| GLASS FRAMES             | 40 mm.  |
| CONSTRUCTION             | Motor, transmission and automatic locking are integrated within the frame.  |
| LOCKING                  | Mechanical lock which automatically locks the window in the closed position and at 50 mm intervals across the opening.  |
| POWER SUPPLY             | Battery backup PS2460. Ensures power supply in case of power failure.   |
| CONTROL SYSTEM           | S3 control system with soft start/stop and hold-to-run buttons as standard.<br>Connection for alarm closing (fire-alarm) and control switch D3.DP1.<br>Adjustable speed, one-touch buttons and various control switches are available as options. |
| GLASS                    | 6 mm Pyran S, fire resistance classification E60.   |
| SURFACE COATING          | Powder coating in white is standard. Powder coating in other RAL-colours are optional.  |
| PROTECTION AGAINST FIRE  | Fire resistance classification E 60. The sliding window is certified by RISE, Research Institutes of Sweden AB.   |
| MANUFACTURED BY          | Please contact our sales personnel for country specific information.<br>Svalson Safety AB, Sweden   |

Visit [www.svalson.com](http://www.svalson.com) for more information.

*Design and material subject to change without prior notice.*

